


## LX 234-XL



Rating: Not Rated Yet

[Ask a question about this product](#)

<p>Description</p> <p>Input Connectors</p> <p>Input Type</p> <p>Input Impedance</p> <p>Max Input</p> <p>CMRR</p> <p>Output Connectors</p> <p>Output Type</p> <p>Output Impedance</p> <p>Max Output</p> <p>Bandwidth</p> <p>Frequency Response</p> <p>Dynamic Range</p> <p>Signal to Noise Ratio</p> <p>THD+Noise</p> <p>Interchannel Crosstalk</p> <p>Bypass Switch</p>	<p>: 1/4" TRS, female XLR (pin 2 hot)</p> <p>: Electronically balanced/unbalanced, RF filtered</p> <p>: Balanced 40 kOhm, unbalanced 20 kOhm</p> <p>: &gt;+21dBu balanced or unbalanced</p> <p>: &gt;40dB, typically &gt;55dB at 1kHz</p> <p>: 1/4" TRS, male XLR (pin 2 hot)</p> <p>: Impedance-balanced/unbalanced, RF filtered</p> <p>: Balanced 100 ohm, unbalanced 50 ohm</p> <p>: &gt;+21dBu balanced/unbalanced into 2 kOhm or greater; &gt;+18dBm balanced/unbalanced (into 600 ohm)</p> <p>: 20Hz to 20kHz, +0.5/-1dB</p> <p>: 50kHz, +0.5/-3dB</p> <p>: Typically &gt;112dB</p> <p>: Typically &gt;95dB</p> <p>: &lt;0.003%</p> <p>: &lt;-90db, 20Hz to 20kHz</p> <p>: Bypasses the graphic equalizer section in the signal path</p>
--	--

Low cut Switch	: Activates the 50Hz 12dB/octave Bessel high-pass filter
Range Switch	: Selects either +/- 6dB or +/- 12dB slider boost/cut range
Operating Voltage	: 100VAC-240VAC 50/60Hz
Power Consumption	: 15W
Power Connector	: IEC receptacle
Unit Weight	: 4.8 lbs.(2.2 kg)
Shipping Weight	: 6.2 lbs.(2.8kg)
Dimensions	: 1.75" (4.4cm) H x 6" (15.24cm) D x 19" (48.26cm) W